

Model IQ50

Deluxe Slimline Telephone

Feature List

- Backlit keypad (Illustrated, see right)
- Tone dialling
- Large keys for easy use
- 100mS PBX recall & pause/redial keys
- Ringer volume control and ringer light
- Wall bracket included
- Ten (10) year parts and labour warranty
- Rugged durable construction
- Noise cancelling handset microphone
- Hearing aid compatible
- Individual serial number on each unit
- Built-in message waiting and ringer indicator lamp
- Keypad and line reset button located on the handset
- Message waiting light built-in to suit many popular PABXs and optional add-ons to suit many other systems
- "Tropicguard" protection for humid conditions such as hotel bathrooms
- Dialless version available for hotline, lobby or information booth application



Available in Black, Grey and Cream

Brief Specifications of Interquartz IQ50	
Dial Mode	Tone (DTMF)
PBX Recall	100 milliseconds Timed Break
Message Waiting light	Suits: Ericsson BP250, Alcatel, Exicom, Fujitsu, NEC, Nortel, Samsung, Lucent Index, Hybrex, LG Aria, Panasonic TD500 & TDA Series, Avaya 8700 & IP Office and Aristel 265 System with A4SLU card only Optional: AT&T, Siemens ISDX, Siemens Hicom, Ericsson MD110 and some Hybrex
Ringer Lamp	Neon tube
Dimensions	Width: 68mm; Length: 222mm; Height: 73mm
Ringer	Electronic with Hi/Lo/Off settings; 80 dBA minimum at a distance of 30cm
Weight	The weight of the unit is 0.6kg approximately
Line Cord and Plug	3m line cord & plug (suits RJ11/12/14/45)
Wall Mount Kit	Included
Operating Temp and Humidity	Temperature: 0-40° C; Humidity: 95% RH max, No dew forming
Regulatory Compliance	Complies with current ACA/Austel standards
Acoustic Shock Protection	Instantaneous – 76 dBA (ACA standard 123 dB SPL), Continuous – 103 dBA (ACA standard 120 dBA)
Colour	Black, Grey & Cream ABS plastic