

Model IQ283P

Hotel Guest Room Telephone

Feature List

- 6 year warranty
- Handsfree speaker phone
- Customised faceplate insert
- Message waiting light
- Available in black or ash
- Ringer pitch control
- Line powered
- Data port
- Recall key
- Redial key
- Ringer light
- Mute key
- Wall mountable
- Ringer volume control
- Hearing aid compatible
- Room number card insert
- Permanent memory retention
- 10 pre-programmable guest service keys
- Electronic speaker volume control



Brief Specifications of Interquartz IQ283P

Dial Mode	Tone (DTMF)
Data Port	Shared mode standard, optional split mode
10 Memory Buttons	32 digits each
Pause	Manual and storable pause of 1 second
PBX Recall	100 milliseconds Timed Break
Memory Retention	Non-volatile memory (permanent retention without power)
Power Source	Line powered. Batteries NOT required
Redial Function	32 digits
Ringer Lamp	Super bright LED and Neon tube
Message Waiting light	Suits: Ericsson BP250, Alcatel, Exicom, Fujitsu, NEC, Nortel, Samsung, Lucent Index, Hybrex, LG Aria, Panasonic TD500 & TDA Series, Avaya 8700 & IP Office and Aristel 265 System with A4SLU card only Optional: AT&T, Siemens ISDX, Siemens Hicom, Ericsson MD110 and some Hybrex
Dimensions	Width: 160mm; Length: 231mm; Height: 83.5mm
Ringer	Electronic with Hi/Lo/Off settings; 80 dBA at 30cm
Line Cord and Plug	3m line cord & plug (suits RJ11/12/14/45)
Wall Mount Kit	Wall Mount Kit No. 3 (order separately)
Operating Temp and Humidity	Temperature: 0-40° C; Humidity: 95% RH max, No dew forming
Regulatory Compliance	Complies with current ACA/Austel standards
Acoustic Shock Protection	Complies with AS/ACIF S004: 2004. Instantaneous – 123 dB SPL, Continuous – 120 dBA
Colour	Ash and Black ABS plastic